SCHNEPP
ELEKTRONISCHE BAUTEILE

Datasheet
ISSUE 2026-11-25

2 TO 3 MM PLUGS AND SOCKETS

BU 2800

2 mm safety press-in socket, 600 V

2 mm socket	5 A	600 V
PLUG DIAMETER	RATED CURRENT	RATED VOLTAGE



Shown: black

TECHNICAL DATA

Electrical and mechanical data

Plug diameter	**2 mm socket**
Rated voltage	**600 V**
Measurement category	**CAT II**
Rated current	**5 A**
Temperature range	**–15 °C to +70 °C**
Mounting hole	**Ø 8.3 mm**

Materials and finish

Body	**Brass**
Contact surface	**gold-plated**
Housing material	**PA6 GF15 (glass-fibre reinforced polyamide)**
Connection	**Solder pin Ø 1.9 mm × 9 mm**

Conformity

RoHS	**compliant**
Marking	**CE**

Dimensions and dimensioned drawing on request.

CUSTOMISATION

Adapted to your application

Also fully custom connectors based on our bundle-wire and spring-basket technology, with matching sockets.

info@schnepp-neudenau.de · +49 6264 9203-0

Marking
Sockets in many colours

Name and logo printing
On request

Matching plugs and test leads
From our range, customised on request as well

Schnepp GmbH
Auweg 5
74861 Neudenau
Germany

PHONE +49 6264 9203-0
EMAIL info@schnepp-neudenau.de
WEB schnepp-neudenau.de

Quality management certified to ISO 9001:2015