SCHNEPP
ELEKTRONISCHE BAUTEILE

Datasheet
ISSUE 2026-11-24

4 MM SAFETY SOCKETS

BU 4852

4 mm safety press-in socket, 14.4 mm flange, thread M3×4

32 A RATED CURRENT

1000 V RATED VOLTAGE



Shown: rendering, red

TECHNICAL DATA

Electrical and mechanical data

Rated voltage	**1000 V**
Measurement category	**CAT II**
Rated current	**32 A**
Mounting hole	**Ø 12.3 mm**

Materials and finish

Contact surface	**Nickel-, silver-, tin- or gold-plated brass available**

Dimensions and dimensioned drawing on request.

COLOURS 8

black · red · blue · yellow · green · violet · white · yellow/green

CUSTOMISATION

Adapted to your application

Also fully custom connectors based on our bundle-wire and spring-basket technology, with matching sockets.

info@schnepp-neudenau.de · +49 6264 9203-0

Marking
Sockets in many colours

Name and logo printing
On request

Matching plugs and test leads
From our range, customised on request as well

Schnepp GmbH
Auweg 5
74861 Neudenau
Germany

PHONE +49 6264 9203-0
EMAIL info@schnepp-neudenau.de
WEB schnepp-neudenau.de

Quality management certified to ISO 9001:2015