SCHNEPP
ELEKTRONISCHE BAUTEILE


Datasheet
ISSUE 2026-11-25

4 MM SAFETY SOCKETS

BU 4909

4 mm safety socket, screw mounting, flat tab 4.8×10 mm

4 mm socket	32 A	1000 V
PLUG DIAMETER	RATED CURRENT	RATED VOLTAGE



Shown: red

TECHNICAL DATA

Electrical and mechanical data

Plug diameter	**4 mm socket**
Rated voltage	**1000 V**
Measurement category	**CAT II**
Rated current	**32 A**
Mounting	**Screw mounting with hex nut or slotted nut as ordered, fitted or supplied loose**
Mounting hole	**Ø 12 mm**
Panel thickness	**up to 8 mm**

Materials and finish

Connection	**4.8×10 mm flat tab**

Dimensions and dimensioned drawing on request.

COLOURS

8

black · red · blue · yellow · green · violet · white · yellow/green

CUSTOMISATION

Adapted to your application

Also fully custom connectors based on our bundle-wire and spring-basket technology, with matching sockets.

info@schnepp-neudenau.de · +49 6264 9203-0

Marking
Sockets in many colours

Name and logo printing
On request

Matching plugs and test leads
From our range, customised on request as well

Schnepp GmbH
Auweg 5
74861 Neudenau
Germany

PHONE +49 6264 9203-0
EMAIL info@schnepp-neudenau.de
WEB schnepp-neudenau.de

Quality management certified to ISO 9001:2015