SCHNEPP
ELEKTRONISCHE BAUTEILE

Datasheet
ISSUE 2026-11-23

DS GOLD CONTACT SYSTEM

DS 6

Gold-contact system DS 6 (6 mm), 60 A

60 A
RATED CURRENT

30 V AC / 60 V DC
RATED VOLTAGE



TECHNICAL DATA

Electrical and mechanical data

Plug diameter	**6 mm spring-basket plug**
Rear connection	**6 mm socket**
Rated voltage	**30 V AC / 60 V DC**
Rated current	**60 A**
Temperature range	**–10 °C to +50 °C**

Materials and finish

Contact material	**Copper beryllium (CuBe)**
Body	**Brass**
Contact surface	**gold-plated**
Cable connection	**Solder connection up to 4 mm²**

Dimensions and dimensioned drawing on request.

COLOURS 2

black red

CUSTOMISATION

Adapted to your application

Also fully custom connectors based on our bundle-wire and spring-basket technology, with matching sockets.

info@schnepp-neudenau.de · +49 6264 9203-0

Marking
Grips in many colours, marked to your system

Name and logo printing
Your name, brand or logo on the grip

Length to order
As a test lead in the length your application needs

Special leads
PVC or silicone cable from 0.25 to 2.5 mm² to your specification

Schnepp GmbH
Auweg 5
74861 Neudenau
Germany

PHONE +49 6264 9203-0
EMAIL info@schnepp-neudenau.de
WEB schnepp-neudenau.de

Quality management certified to ISO 9001:2015