SCHNEPP
ELEKTRONISCHE BAUTEILE

Datasheet
ISSUE 2026-11-22

PANEL-MOUNT AND STAINLESS PLUGS

EFK 3000

3 mm panel-mount spring-basket plug

Ø 3 mm	30 A	30 V AC / 60 V DC
PLUG DIAMETER	RATED CURRENT	RATED VOLTAGE



TECHNICAL DATA

Electrical and mechanical data

Plug diameter	**Ø 3 mm**
Rated voltage	**30 V AC / 60 V DC**
Rated current	**30 A**
Temperature range	**–10 °C to +50 °C**

Materials and finish

Contact material	**Brass**
Contact surface	**Nickel**
Connection	**Screw**

Dimensions and dimensioned drawing on request.

FEATURES

- Also available gold-plated
- Thread M3.5

CUSTOMISATION

Adapted to your application

Also fully custom connectors based on our bundle-wire and spring-basket technology, with matching sockets.

info@schnepp-neudenau.de · +49 6264 9203-0

Marking
To your system

Special version
To your drawing or specification

Schnepp GmbH
Auweg 5
74861 Neudenau
Germany

PHONE +49 6264 9203-0
EMAIL info@schnepp-neudenau.de
WEB schnepp-neudenau.de

Quality management certified to ISO 9001:2015