SCHNEPP
ELEKTRONISCHE BAUTEILE

Datasheet
ISSUE 2026-11-25

SAFETY TEST LEADS

MFK 1165 / 2,5 mm²

4 mm safety test lead like MFK 1164 / 2.5 mm², with red insulating cap on the plug

Ø 4 mm	32 A	1000 V
PLUG DIAMETER	RATED CURRENT	RATED VOLTAGE

TECHNICAL DATA

Electrical and mechanical data

Plug diameter	**Ø 4 mm**
Rated voltage	**1000 V**
Rated current	**32 A**
Temperature range	**–10 °C to +50 °C**

Materials and finish

Contact material	**Brass, CuBe**
Contact surface	**Nickel**
Housing material	**PA (polyamide)**
Cable material	**PVC, 2.5 mm²**

Conformity

Marking	**CE**

Dimensions and dimensioned drawing on request.

COLOURS

10

black · red · blue · yellow · green
grey · brown · violet · orange · white

FEATURES

- Cable 2.5 mm², double-insulated

CUSTOMISATION

Adapted to your application

Also fully custom connectors based on our bundle-wire and spring-basket technology, with matching sockets.

info@schnepp-neudenau.de · +49 6264 9203-0

Marking
Colours and marking sleeves to your system

Name and logo printing
Your name, brand or logo on the test lead

Length to order
Cable length exactly as you specify

Special leads
Cable, cross-section and plugs at both ends to your specification

Schnepp GmbH
Auweg 5
74861 Neudenau
Germany

PHONE +49 6264 9203-0
EMAIL info@schnepp-neudenau.de
WEB schnepp-neudenau.de

Quality management certified to ISO 9001:2015