SCHNEPP
ELEKTRONISCHE BAUTEILE

**Datasheet**
ISSUE 2026-11-25

SAFETY TEST LEADS

# MFK 1165 / 1 mm²

4 mm safety test lead like MFK 1164 / 1 mm², with red insulating cap on the plug

| Ø 4 mm | 16 A | 1000 V |
|---|---|---|
| PLUG DIAMETER | RATED CURRENT | RATED VOLTAGE |

## TECHNICAL DATA

### Electrical and mechanical data

| | |
|---|---|
| Plug diameter | **Ø 4 mm** |
| Rated voltage | **1000 V** |
| Rated current | **16 A** |
| Temperature range | **–10 °C to +50 °C** |

### Materials and finish

| | |
|---|---|
| Contact material | **Brass, CuBe** |
| Contact surface | **Nickel** |
| Housing material | **PA (polyamide)** |
| Cable material | **PVC, 1 mm²** |

### Conformity

| | |
|---|---|
| Marking | **CE** |

Dimensions and dimensioned drawing on request.

## COLOURS

10

black · red · blue · yellow · green
grey · brown · violet · orange · white

CUSTOMISATION

## Adapted to your application

Also fully custom connectors based on our bundle-wire and spring-basket technology, with matching sockets.

info@schnepp-neudenau.de · +49 6264 9203-0

**Marking**
Colours and marking sleeves to your system

**Name and logo printing**
Your name, brand or logo on the test lead

**Length to order**
Cable length exactly as you specify

**Special leads**
Cable, cross-section and plugs at both ends to your specification

**Schnepp GmbH**
Auweg 5
74861 Neudenau
Germany

PHONE +49 6264 9203-0
EMAIL info@schnepp-neudenau.de
WEB schnepp-neudenau.de

Quality management certified to ISO 9001:2015