SCHNEPP
ELEKTRONISCHE BAUTEILE

Datasheet
ISSUE 2026-11-23

SHORTING PLUGS

SI-FK 19/4

4 mm safety shorting plug, 19 mm pitch

25 A	1000 V	−20 °C to +50 °C
RATED CURRENT	RATED VOLTAGE	TEMPERATURE RANGE



Shown: rendering, red

TECHNICAL DATA

Electrical and mechanical data

Plug diameter	**2 × 4 mm spring-basket plug, insulated**
Rated voltage	**1000 V**
Measurement category	**CAT II**
Rated current	**25 A**
Temperature range	**−20 °C to +50 °C**

Materials and finish

Contact material	**Copper beryllium (CuBe)**
Body	**Brass**
Contact surface	**nickel-plated**
Housing material	**PE (polyethylene)**
Cable connection	**none**

Dimensions and dimensioned drawing on request.

COLOURS 3

black · red · white

CUSTOMISATION

Adapted to your application

Also fully custom connectors based on our bundle-wire and spring-basket technology, with matching sockets.

info@schnepp-neudenau.de · +49 6264 9203-0

Marking
Grips in many colours, marked to your system

Name and logo printing
Your name, brand or logo on the grip

Schnepp GmbH
Auweg 5
74861 Neudenau
Germany

PHONE +49 6264 9203-0
EMAIL info@schnepp-neudenau.de
WEB schnepp-neudenau.de

Quality management certified to ISO 9001:2015